

556, 223

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number
WO 2004/110637 A1


- (51) International Patent Classification⁷: **B04B 1/20**
- (21) International Application Number:
PCT/SE2004/000814
- (22) International Filing Date: 27 May 2004 (27.05.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0301779-5 18 June 2003 (18.06.2003) SE
- (71) Applicant (for all designated States except US): **ALFA LAVAL CORPORATE AB** [SE/SE]; Rudeboksvägen 1, S-221 00 Lund (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **STROUCKEN, Klaus** [SE/SE]; Tallsätravägen 12, S-144 63 Rönninge (SE). **RIDDERSTRÅLE, Rolf** [SE/SE]; Heleneborgsgatan 21, S-117 31 Stockholm (SE). **GEIDING, Robert**

[SE/SE]; Morgonvägen 35, S-146 32 Tullinge (SE). **HÖGLUND, Kasper** [SE/SE]; Hagsätravägen 9, S-144 63 Rönninge (SE).

- (74) Agent: **CLIVEMO, Ingemar**; Alfa Laval Corporate AB, Hans Stahles väg, S-147 80 Tumba (SE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: A SCREW CONVEYOR FOR A DECANter CENTRIFUGE



(57) Abstract: A screw conveyor (2) intended and formed for use in a decanter centrifuge for separation of solid particles from a fluid compound, comprising a central body (10), at least one conveyor thread (11a; 11b) and at least one baffle (12) bridging a flow path formed between different parts of the conveyor thread. The screw conveyor (2) has at least two originally separate parts (22, 23), each of which comprises a portion of said conveyor thread (11a; 11b) and which are kept together axially. The baffle (12) constitutes a separate member arranged to be kept in place between said parts (22, 23) of the screw conveyor, when these parts are kept together axially, and has a portion (26; 27) which forms a part of the conveyor thread (11a; 11b) in an area where the conveyor thread intersects with and extends past the baffle (12).

WO 2004/110637 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*